



LPS1175 Double Security Turnstiles EAG09000-1491



Key features

- A1(SR1), B3(SR2) and C5(SR3) externally accredited to LPS1175: Issue 7 certificate 1495a
- 90° Locking head mechanism, electrically released in both directions
- Rotor sensing relays to provide a voltage free contact following the rotation of the rotor in either direction
- Status light LED panels to indicate when to proceed
- 240V AC mains supply 2 amp
- Fail locked on power failure
- Walkway canopy with down lights
- Side panels clad in galvanised weld mesh (SR2 & SR3): this is see through for CCTV
- Bolts directly onto concrete base
- Finish powder coated standard RAL colour
- Can be assembled on site, if delivered flat pack
- Refer to individual drawings for more information



Double turnstile (W 2,000mm D 1,330mm)

- Fits inside a standard fence panel
- 1491-211-S A1(SR1) Straight bar rotor arms
- 1491-212-SF B3(SR2) Straight bar filled rotor arms
- 1491-213-SFA C5(SR3) Straight bar filled armor rotor arms



LPS 1175 Issue 8
Certificate 1572



LPS 1175 Cert/LPCB ref. 1572



Raising Standards
Safety Assured



Eagle Automation Limited - Head Office: Unit 5, New House Farm, Vicarage Lane, North Weald, Essex, CM16 6AP, UK.
Telephone: +44 (0)1992 524 800 **Website:** <https://eagleautogate.co.uk> **Email:** sales@eagleautogate.co.uk

Made in the UK, exported globally

