



LPS1175 Single Security Turnstiles EAG09000-1491



Key features

- A1(SR1), B3(SR2), C5(SR3) and D10(SR4) externally accredited to LPS1175: Issue 8 certificate 1572
- Available as double units (A1(SR1)—C5(SR3) only)
- 90° Locking head mechanism, electrically released in both directions
- Rotor sensing relays to provide a voltage free contact following the rotation of the rotor in either direction
- Status light LED panels to indicate when to proceed
- 240V AC mains supply 2 amp
- Fail locked on power failure
- Walkway canopy with down light
- Side panels clad in galvanised weld mesh (B3(SR2)-D10(SR4)): this is see through for CCTV
- Bolts directly onto concrete base
- Finish powder coated standard RAL colour
- Can be assembled on site, if delivered flat pack
- Refer to individual drawings for more information



LPS 1175 Issue 8
Certificate 1572

Single turnstiles (W 1,350mm D 1,330mm)

- 1491-201-S A1(SR1) straight bar rotor arms
- 1491-201-H A1(SR1) Hooped bar rotor arms
- 1491-202-SF B3(SR2) straight bar filled rotor arms
- 1491-202-HF B3(SR2) Hooped bar rotor paddles
- 1491-203-SFA C5(SR3) Straight Bar filled armor rotor arms
- 1491-203-HFA C5(SR3) Hooped Bar filled sheet and armor rotor paddles
- 1491-204-HFA D10(SR4) Hooped D Bar filled armor shaped rotor paddles



LPS 1175 Cert/LPCB ref. 1572



Raising Standards
Safety Assured



Eagle Automation Limited - Head Office: Unit 5, New House Farm, Vicarage Lane, North Weald, Essex, CM16 6AP, UK.
Telephone: +44 (0)1992 524 800 **Website:** <https://eagleautogate.co.uk> **Email:** sales@eagleautogate.co.uk

Made in the UK, exported globally

